PLATFORM™ PERFORMANCE FLOORING SYSTEMS
A KEENE INC. COMPANY

Gypsum Patch and Skimcoat
with Latex Additive

White SkimCoat™ + White Latex Liquid®

White SkimCoat™ is the patch professionals choice for economical, fast setting, high strength gypsum based patch. When White SkimCoat is used with Platform Performance Floors's White Latex Liquid admixture, it provides increased adhesion and flexural strengths for use over problematic substrates.

White Latex Liquid® is a non re-emulsifiable latex additive used in lieu of water as an admixture with White SkimCoat or Skimcrete XP to increase patch performance and durability. The addition of White Latex Liquid will increase the adhesion and flexibility of White Skim Coat and Skimcrete XP.

Gypsum Patch and SkimCoat with Latex Additive to Improve Patch Bond and Strength

FEATURES OF WHITE SKIMCOAT

- Outstanding flexural strength
- Designed for approved wood and gypsum substrates
- Durable high strength specialty cement
- Acceptable for use on UL Fire Rated Assemblies
- Non-alkaline – adhesive friendly
- Withstands construction/renovation traffic

FEATURES OF WHITE LATEX LIQUID®

- Additive for White SkimCoat and Skimcrete XP
- Improves patch bond, flexural and surface strength
- Enhanced water resistance and patch durability
- Mildewcide Protection

Properties for White SkimCoat

Working Time	15 Minutes
Time to foot traffic	30 Minutes at 1/8" thickness
Application Conditions	Dry, interior environment above 50°F (10°C)
Coverage (25 lb bag)	Feather Edge 110 - 130 ft² 1/8" (3mm) 25 - 3 ft²
Water per 10lb unit	5.5 qts. of water to 25 lb. bag 2.25 qts. of water to 10 lb. bag
Color	White
Thickness	Feather edge to 1" (25 mm) in thickness
Shelf Life	9 Months when unopened & stored per instructions
SKU - White Skimcoat	50 lb Pail: DWS50 25 lb bag: DWS25
SKU - White Latex Liquid	4x1Gal. box: DWL4x1 5 Gal. Pail: DWL5

All specifications were tested in laboratory conditions: 73°F in a controlled environment using our approved water content. Changing the temperature, or mixing ratios, or the environment can effect these specifications. Call Technical Services if you have any questions.

LEED Credit LCD Rapid may contribute to LEED certification of projects as follows:

AREA	CREDIT	CATEGORY	HOW
Indoor Environmental Quality	EQ 4.2	Low Emitting Materials	VOC content 0g/l (calculated)
Materials & Resources	MR 4.1, 4.2	Recycled Content	0%
Regional Manufactured Material	MR 5.2	Regional Materials	45%

Platform Performance Flooring Systems
2926 Chester Avenue, Cleveland, OH 44114
(877) 514-5336

Visit: PlatformPerformance.com
info@PlatformPerformance.com

© 2026 Dependable, LLC™, All rights reserved.
Printed in U.S.A. All logos/images are trademarks of Dependable, LLC. Cleveland, OH USA.
DEP-652098-09-0226