SANDED GROUT

elastiment

LIMITATIONS

SANDED GROUT SHOULD NOT be used in areas where high acid resistance is required because of its Portland cement base.

ADVANTAGES

Sanded Grout out-performs conventional sand/cement grouts in areas of intermittent mild acid exposure.

SPECIFICATIONS

Sanded Grout may be used in installations that must conform to A.N.S.I. specifications. It meets A.N.S.I. A118.6 (See TCA Handbook for tile installations)

LIMITED WARRANTY:

The suitability of the product for an intended use shall be solely up to the user. Job site conditions including surface preparation, temperature, humidity, and tile quality can adversely affect the products performance. Warranties of merchantability and of fitness are hereby disclaimed. Manufacturer and seller assume no liability for consequential damages. Manufacturer agrees to replace or pay for any material proved to be defective. with no liability beyond the purchase price of defective materials. This warranty is in place of all other warranties. expressed or implied. No person has the authority to change these items and there are no warranties except as herein stated.

24 HOUR EMERGENCY:
CHEMTREC®
1-800-424-9300
NON-TOXIC and
NON-FLAMMABLE

Keep container closed and keep away from children. May cause slight eye abrasion or irritation if spilled or rubbed in eyes. Flush thoroughly with water.

Sanded Grout is a blend of Portland cement, specially graded silica sand, and colorfast pigments that form a dense matrix free of any voids. Special chemicals have been added to provide for a superior grout that offers ease of workability and clean-up, rapid curing, high compressive strength, low shrinkage, good bond strength and color control. This non-toxic, non-dusting, iron-free grout, is highly resistant to bacteria, fungus, oils and alkalis.

Use

Sanded Grout can be used in both residential and heavy commercial installation, where joint widths are in excess of 1/8". This specially designed high performance grout is to be used with quarry, slate, pavers, brick and cement tiles for interior and/or exterior use. To produce a dense smooth grout, water is required to be used. However, Elastiment Grout admixtures can be used as an alternative to intensify the bond and flexural strength for installations subjected to thermal shock.

TEXTURE
Sanded Grout is a powder consisting of Portland cement, graded silica sand, pigment, organic and inorganic chemicals.

COLOR
Sanded Grout is available in 20 standard colors. Designer colors are available upon request.

PACKAGING
25 lb. bag and 10 lb. pail

MIXING
Blend with clean water only to desired consistency. Other admixes are available upon request for special applications.

TEMPERATURE
Use in temperatures above 40° F. (Do not allow resin mortar to freeze for the first 72 hours.)

CURING
Damp curing is required.

SAFETY
It contains Portland cement: freshly mixed mor tar may cause skin injury. Avoid contact with skin where possible. Wash exposed skin areas promptly with water. If mortar gets in eyes, rinse immediately and repeat. Get prompt medical attention.

KEEP OUT OF REACH OF CHILDREN.

Published technical data & instructions are subject to change without notice. Please contact Boiradi for the most current technical data, safety data & application instructions.

BOIARDI PRODUCTS CORPORATION