

# Safety Data Sheet (SDS)

According to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

## Section 1: Identification of the Substance/Mixture and the Company/Undertaking

**Product Name: Platform ELW      Product Code: Platform ELW**

Platform Performance Flooring Systems  
2926 Chester Ave.  
Cleveland, OH 44114  
USA

Email:  
info@platformperformance.com

Phone:  
440-605-1020

Chemtrec: 1- 800-424-9300  
Chemtrec Global: 1-703-741-5970



## Section 2: Hazard(s) Identification

### GHS Ratings:

|                 |    |                                                                                                                         |
|-----------------|----|-------------------------------------------------------------------------------------------------------------------------|
| Skin corrosive  | 2  | Reversible adverse effects in dermal tissue, Draize score: $\geq 2.3 < 4.0$ or persistent inflammation                  |
| Eye corrosive   | 1  | Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity $\geq 3$ , Iritis $> 1.5$ |
| Skin sensitizer | 1  | Skin sensitizer                                                                                                         |
| Carcinogen      | 1A | Known Human Carcinogen Based on human evidence                                                                          |

### GHS Hazards

|      |                                      |
|------|--------------------------------------|
| H315 | Causes skin irritation               |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage            |
| H350 | May cause cancer                     |

### GHS Precautions

|                |                                                                                                                                   |
|----------------|-----------------------------------------------------------------------------------------------------------------------------------|
| P201           | Obtain special instructions before use                                                                                            |
| P202           | Do not handle until all safety precautions have been read and understood                                                          |
| P261           | Avoid breathing dust/fume/gas/mist/vapours/spray                                                                                  |
| P264           | Wash thoroughly after handling.                                                                                                   |
| P272           | Contaminated work clothing should not be allowed out of the workplace                                                             |
| P280           | Wear protective gloves/protective clothing/eye protection/face protection                                                         |
| P281           | Use personal protective equipment as required                                                                                     |
| P310           | Immediately call a POISON CENTER or doctor/physician                                                                              |
| P321           | Specific treatment, see supplemental first aid information.                                                                       |
| P362           | Take off contaminated clothing and wash before reuse                                                                              |
| P363           | Wash contaminated clothing before reuse                                                                                           |
| P302+P352      | IF ON SKIN: Wash with soap and water                                                                                              |
| P305+P351+P338 | IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing |

P308+P313  
P332+P313  
P333+P313  
P405  
P501

IF exposed or concerned: Get medical advice/attention  
If skin irritation occurs: Get medical advice/attention  
If skin irritation or a rash occurs: Get medical advice/attention  
Store locked up  
Dispose of contents/container in accordance with local/regional/national/international regulations. Manufacturer/supplier or the competent authority to specify whether disposal requirements apply to contents, container or both.

Signal Word: Danger



### Section 3: Composition/Information on Ingredients

| Chemical Name                    | CAS number | Weight Concentration % |
|----------------------------------|------------|------------------------|
| Limestone                        | 1317-65-3  | 10.00% - 30.00%        |
| Quartz                           | 14808-60-7 | 10.00% - 30.00%        |
| Cement, alumina, chemicals       | 65997-16-2 | 10.00% - 30.00%        |
| Glass, oxide, chemicals          | 65997-17-3 | 10.00% - 30.00%        |
| Calcium Sulfate Hemihydrate      | 26499-65-0 | 1.00% - 5.00%          |
| Portland cement                  | 65997-15-1 | 1.00% - 5.00%          |
| Ethylene-vinyl acetate copolymer | 24937-78-8 | 1.00% - 5.00%          |

### Section 4: First Aid Measures

#### 4.1 Description of First Aid Measures

**After Inhalation:** Supply fresh air. If required provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

**After Eye Contact:** Remove contact lens if worn. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After Skin Contact:** Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

**After Swallowing:** Rinse out mouth and then drink plenty of water. Do not induce vomiting. Call for medical help immediately.

**Notes to Physician:** Treat symptomatically

### Section 5: Firefighting Measures

Flash Point: 998 C (1,828 F)

LEL:

UEL:

#### 5.1 Extinguishing Media

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

## **5.2 Special Hazards Arising from the Substance of Mixture**

Formation of toxic gases is possible during heating or in case of fire.

## **5.3 Hazardous Combustion Products**

Carbon oxides

## **5.4 Advice for Firefighters**

Wear self-contained respiratory protective device

## **5.5 Fire Equipment**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations

# **Section 6: Accidental Release Measures**

## **6.1 Personal Precautions, Protective Equipment and Emergency Procedures**

Do not breathe vapors

Avoid contact with skin, eyes and clothing

Remove all non-essential people from the affected area.

Ensure adequate ventilation

Wear protective equipment

**6.2 Environmental Precautions:** Do not allow to enter sewers/ surface or ground water. Prevent seepage into sewage system, workpits and cellars

## **6.3 Methods and Materials for Containment and Cleaning Up:**

Ensure adequate ventilation.

Pick up and arrange disposal without creating dust.

Dispose of the collected material according to regulations

## **6.4 Reference to Other Sections**

For personal protection see Section 8

For disposal information see Section 13.

# **Section 7: Handling and Storage**

## **7.1 Precautions for Safe Handling**

Do not breath vapour/spray

Do not get in eyes, on skin, or on clothing

Ensure good ventilation/exhaustions at the workplace

Make sure that all applicable workplace limits are observed.

## **7.2 Conditions for Safe Storage, Including any Incompatibilities**

Store in cool, dry conditions in well sealed receptacles

Keep receptacle tightly sealed. Store in dry conditions.

Protect from humidity and water

Storage temperature 10 - 50 °C

Do not store together with oxidizing and acidic materials.

**Requirements to be Met by Storerooms and Receptacles:** Observe all local and national regulations for storage of water polluting products.

## **7.3 Specific End Use(s)**

No further relevant information available.

## Section 8: Exposure Controls/Personal Protection

| Chemical Name / CAS No.                        | OSHA Exposure Limits                                                                 | ACGIH Exposure Limits                                                                                               | Other Exposure Limits                                                                   |
|------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|
| Limestone<br>1317-65-3                         | 15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction) | Not Established                                                                                                     | NIOSH: 10 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable dust) |
| Quartz<br>14808-60-7                           | Not Established                                                                      | 0.025 mg/m <sup>3</sup> TWA (respirable fraction)                                                                   | NIOSH: 0.05 mg/m <sup>3</sup> TWA (respirable dust)                                     |
| Cement, alumina, chemicals<br>65997-16-2       | PEL 15 mg/m <sup>3</sup>                                                             | Not Established                                                                                                     | Not Established                                                                         |
| Glass, oxide, chemicals<br>65997-17-3          | Not Established                                                                      | Not Established                                                                                                     | Not Established                                                                         |
| Calcium Sulfate Hemihydrate<br>26499-65-0      | 15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction) | Not Established                                                                                                     | NIOSH: 10 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable dust) |
| Portland cement<br>65997-15-1                  | 15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction) | 1 mg/m <sup>3</sup> TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction) | NIOSH: 10 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable dust) |
| Ethylene-vinyl acetate copolymer<br>24937-78-8 | Not Established                                                                      | Not Established                                                                                                     | Not Established                                                                         |

### 8.1 General Protective and Hygienic Measures

The usual precautionary measures are to be adhered to when handling chemicals.

Do not eat, drink, smoke or sniff while working

Keep away foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin

### 8.2 Personal Protective Equipment

Eye Protection: Safety glasses with side shields. If splashes are likely to occur, wear goggles.

Respiratory Protection: Use suitable respirator protective device in case of insufficient ventilation. Use suitable respiratory protective device when aerosol or mist is formed.

Protection of Hands: Protective gloves: to avoid skin problems, the glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of Gloves: Neoprene, butyl rubber gloves, the selection of the suitable gloves does not only depend on the material, but also on the further marks of quality and varies from manufacturer to manufacturer several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application. Penetration time of Glove Material: Protective gloves should be replaced at the first signs of wear. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Additional Information:** The lists that were valid during the creation were used as a basis.

## Section 9: Physical and Chemical Properties

### 9.1 Information on Basic Physical and Chemical Properties

|                                         |                                     |                                             |       |
|-----------------------------------------|-------------------------------------|---------------------------------------------|-------|
| <b>Vapor Pressure</b>                   | 10.0 mmHg                           | <b>VOC</b>                                  | 0.0 % |
| <b>Boiling Range</b>                    | 1000 to 2230 °C,<br>1832 to 4046 °F | <b>Specific Gravity (SG)</b>                | 1.235 |
| <b>Coating VOC (as supplied) lb/gal</b> | 0.00                                | <b>Coating VOC (EPA calculation) lb/gal</b> | 0.00  |

## Section 10: Stability and Reactivity

### 10.1 Reactivity

Stable under recommended storage conditions. No decomposition if stored and applied as directed.

STABLE

### 10.2 Chemical Stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

## Section 11: Toxicological Information

### Mixture Toxicity

Oral Toxicity LD50: 2,157mg/kg

### Component Toxicity

### 11.1 Information on Toxicological Effects

#### Routes of Entry:

No data available

#### Target Organs:

Eyes      Skin      Respiratory System

#### Effects of Overexposure

**Carcinogenicity:** The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

| <u>CAS Number</u> | <u>Description</u> | <u>% Weight</u> | <u>Carcinogen Rating</u>                                                                   |
|-------------------|--------------------|-----------------|--------------------------------------------------------------------------------------------|
| 14808-60-7        | Quartz             | 10 to 30%       | Quartz: NIOSH: potential occupational carcinogen<br>IARC: Human carcinogen<br>OSHA: listed |

## Section 12: Ecological Information

## 12.1 Persistence and Degradability

**Product:** No further relevant information available

## 12.2 Bioaccumulative Potential

**Product:** Bioaccumulation: No further relevant information available

Partition coefficient: n-octanol/water: No further relevant information available

## 12.3 Mobility in Soil

**Product:** Distribution among environmental compartments: No further relevant information available.

### Additional Ecological Information:

**General notes:** German Hazard Water Class 1

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## 12.4 Results of PBT and vPvB Assessment

Assessment: This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB)

## 12.5 Other Adverse Effects

**Product:** No further relevant information available

## 12.6 Toxicity

### Component Ecotoxicity

## Section 13: Disposal Considerations

### 13.1 Waste Treatment Methods

**Product:** The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches the chemical or used container. Offer surplus and non-recyclable solutions to a licensed disposal company. Send to a licensed waste management company.

**Contaminated Packaging:** Empty remaining contents. Dispose of as unused product. Do not re-use empty containers

## Section 14: Transport Information

### 14.1 UN Number

| <u>Agency</u> | <u>Proper Shipping Name</u> | <u>UN Number</u> | <u>Packing Group</u> | <u>Hazard Class</u> |
|---------------|-----------------------------|------------------|----------------------|---------------------|
| Not           | Regulated                   |                  |                      |                     |

## Section 15: Regulatory Information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prop 65 - Chemicals Known to Cause Developmental Toxicity

- None

Prop 65 - Chemicals Known to Cause Cancer:

14808-60-7 Quartz

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

- None

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

- None

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

- None

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

- None

- None

TSCA (Toxic Substances Control Act)

- None

**Country**

USA

Canada

**Regulation**

Inventory - United States - Section 8(b) Inventory (TSCA)

DSL (Canadian Domestic Substance List)

**All Components Listed**

Yes

Yes

**EU Risk Phrases**

**Safety Phrase**

- None

**Section 16: Other Information**

We believe the information contained in this SDS is correct, however, because the material may be used under conditions over which we have no control, we give no warranty and assume no responsibility for any damage to person, property or business arising from such use. It is the responsibility of the user to ensure it is properly used. Recipients are advised to confirm in advance of need that the information is current, applicable and suitable to their circumstances. This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Date Prepared: 2/20/2026